



# Inward Opening

## IV 78



### Tilt & turn operation

secure ventilation  
and easy cleaning  
from inside.



### Three performance levels

IV68, IV78 and IV92 profiles,  
up to passive house standard.



### Internal glazing beads

deep mouldings,  
slim meeting rails,  
true or applied glazing bars.



### Triple glazing ready

whole-window U-values  
down to  $0.74 \text{ W}/(\text{m}^2\cdot\text{K})$ .

|                               |                                                    |
|-------------------------------|----------------------------------------------------|
| Glazing unit:                 | 4-44 mm                                            |
| Pane:                         | UG = $3.0-0.5 \text{ W}/(\text{m}^2\cdot\text{K})$ |
| Spacer:                       | WARM                                               |
| Material:                     | PINE JOINTED / MERANTI / OAK /<br>SAPELE / ACCOYA  |
| Fitting:                      | ROTO / GU / MACO                                   |
| Handle:                       | COLOUR-MATCHED TO FRAME                            |
| Colour:                       | VARNISH COLORS / RAL / F&B                         |
| Silicone:                     | WHITE / BLACK / CLEAR /<br>GREY / BROWN            |
| Frame width:                  | 78 mm                                              |
| Heat Transfer<br>Coefficient: | $0.85 \text{ W}/(\text{m}^2\cdot\text{K})$         |